

CK-U1200MI/CI-10RS

12 MP 1/1.7" CMOS GigE Area Scan Camera




Introduction

CK-U1200MI/CI-10RS camera adopts Sony® IMX226 sensor to provide high-quality images. It uses GigE interface to transmit non-compressed images in real time, and its max. frame rate can reach 9.7 fps in full resolution.

Key Feature

- Adopts low power consumption design with stable performance.
- Supports auto and manual adjustment of gain, exposure time, etc.
- Supports hardware trigger, software trigger, free run, etc.
- Adopts GigE interface and max. transmission distance of 100 meters without relay.
- Compatible with GigE Vision V2.0 Protocol, GenICam Standard, and third-party software based on the protocol and standard.

Dimension




Available Model

- Mono camera: CK-U1200MI-10RS
- Color camera: CK-U1200CI-10RS


Applicable Industry

Electronics and semiconductor, factory automation, logistics and code reading, medicine package, etc.

Sensor Quantum Efficiency



CK-U1200MI-10RS



CK-U1200CI-10RS

Specification

Model	CK-U1200MI-10RS		CK-U1200CI-10RS	
Performance				
Sensor type	CMOS, rolling shutter			
Sensor model	Sony® IMX226			
Pixel size	1.85 μm × 1.85 μm			
Sensor size	1/1.7"			
Resolution	4024 × 3036			
Max. frame rate	9.7 fps @4024 × 3036 Mono 8	9.7 fps @4024 × 3036 Bayer RG 8		
Dynamic range	70.5 dB			
SNR	40.5 dB			
Gain	0 dB to 20 dB			
Exposure time	34 μs to 2 sec			
Exposure mode	Off/Once/Continuous exposure mode			
Mono/color	Mono	Color		
Pixel format	Mono 8/10/10Packed/12/12Packed	Bayer RG 8/10/10Packed/12/12Packed		
Binning	Supports 1 × 1, 2 × 2, 4 × 4			
Decimation	Supports 1 × 1, 2 × 2, 4 × 4			
Reverse image	Supports horizontal and vertical reverse image output			
Electrical feature				
Data interface	Gigabit Ethernet, compatible with Fast Ethernet			
Digital I/O	6-pin P7 connector provides power and I/O, including opto-isolated input × 1 (Line 0), opto-isolated output × 1 (Line 1), bi-directional non-isolated I/O × 1 (Line 2).			
Power supply	9 VDC to 24 VDC, PoE is optional			
Power consumption	Typ. 1.78 W@12 VDC	Typ. 1.82 W@12 VDC		
Mechanical				
Lens mount	C-mount			
Dimension	29 mm × 29 mm × 42 mm (1.1" × 1.1" × 1.7")			
Weight	Approx. 100 g (0.2 lb.)			
Ingress protection	IP30 (under proper lens installation and wiring)			
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: -30 °C to 70 °C (-22 °F to 158 °F)			
Humidity	20% to 95% RH, non-condensing			
General				
Client software	CKVisionBuilder or third-party software meeting with GigE Vision Protocol			
Operating system	32/64-bit Windows XP/7/10, 32/64-bit Linux and 64-bit MacOS			
Compatibility	GigE Vision V2.0, GenICam			
Certification	CE, RoHS, KC			

