CK-U1200MI/CI-10RS(N) V2

12 MP 1/1.7'' GigE Area Scan Camera



Introduction

CK-U1200MI/CI-10RS(N) V2 camera adopts Sony® IMX226 sensor to provide high-quality images. It uses GigE interface to transmit non-compressed images in real time, and its max. frame rate can reach 9.7 fps in full resolution.

Key Features

- Adopts low consumption design with stable performance.
- Supports auto and manual adjustment of gain, exposure time, etc.
- Supports hardware trigger, software trigger, free run, etc.
- Adopts GigE interface and max. transmission distance of 100 meters without relay.
- Compatible with GigE Vision V2.0 Protocol, GenICam Standard, and third-party software based on the protocol and standard.


Applicable Industry

Electronics and semiconductor, factory automation, logistics and code reading, medicine package, etc.


Available Model

- Mono camera: CK-U1200MI-10RS(N) V2
- Color camera: CK-U1200CI-10RS(N) V2

Sensor Quantum Efficiency




CK-U1200MI-10RS(N) V2



CK-U1200CI-10RS(N) V2

Dimension



Specification

Model	CK-U1200MI-10RS(N) V2	CK-U1200CI-10RS(N) V2
Performance		
Sensor type	CMOS, rolling shutter	
Sensor model	Sony® IMX226	
Pixel size	1.85 μm × 1.85 μm	
Sensor size	1/1.7"	
Resolution	4024 × 3036	
Max. frame rate	9.7 fps @ 4024 × 3036 Mono 8	9.7 fps @ 4024 × 3036 Bayer RG 8
Dynamic range	70.5 dB	
SNR	40.5 dB	
Gain	0 dB to 20 dB	
Exposure time	34 μs to 2 sec	
Exposure mode	Off/Once/Continuous exposure mode	
Mono/color	Mono	Color
Pixel format	Mono 8/10/10Packed/12/12Packed	Bayer RG 8/10/10Packed/12/12Packed
Binning	Supports 1 × 1, 2 × 2, 4 × 4	
Decimation	Supports 1 × 1, 2 × 2, 4 × 4	
Reverse image	Supports horizontal and vertical reverse image output	
Electrical feature		
Data interface	Gigabit Ethernet (1000 Mbit/s), compatible with Fast Ethernet (100 Mbit/s)	
Digital I/O	6-pin P7 connector provides power and I/O, including opto-isolated input × 1 (Line 0), opto-isolated output × 1 (Line 1), bi-directional non-isolated I/O × 1 (Line 2).	
Power supply	9 VDC to 24 VDC, PoE is optional	
Power consumption	Typ. 1.78 W @ 12 VDC	Typ. 1.82 W @ 12 VDC
Mechanical		
Lens mount	C-mount	
Dimension	29 mm × 29 mm × 42 mm (1.1" × 1.1" × 1.7")	
Weight	Approx. 100 g (0.2 lb.)	
Ingress protection	IP30 (under proper lens installation and wiring)	
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: –30 °C to 80 °C (–22 °F to 176 °F)	
Humidity	20% RH to 95% RH (no condensation)	
General		
Client software	CKVisionBuilder or third-party software meeting with GigE Vision Protocol	
Operating system	32/64-bit Windows 7/10, 64-bit Windows 11, 32/64-bit Linux	
Compatibility	GigE Vision V2.0, GenICam	
Certification	CE, RoHS, KC	